



JLG E300 SERIES

- Choice of models with up to a working height of 11 m
- Articulating Jib and JibPLUS™ features available for improved positioning
- Multiple function operation gets you to the job quicker
- Proportional controls achieve smoother movement for operator comfort
- Non-marking tyres for travel on indoor floor surfaces
- Automatic Traction Control (ATC) for improved manoeuvrability on off-slab areas
- Compact chassis width helps access in congested areas

For more details check the JLG Technical Specification Guide or ask your local JLG representative.



Automatic Traction Control (ATC) for higher performance

Advanced control system ensures improved traction on uneven surfaces or over floor obstacles.



Exclusive JibPLUS™ Boom*

Provides a 180 degree range of side-to-side movement in addition to near vertical elevation of 75 degrees for the most versatile positioning capabilities available.

* Model E300AJP only



Easy to follow layout of controls

Console designed for ease of operation and rapid positioning control.



Compact Double Knuckle Boom

To help with positioning in tight work spaces, the double knuckle boom design is compact and mechanically synchronised to provide zero tail-swing.



Operator's Tool Tray

Provides a handy storage area for tools, fasteners and other work materials.



Narrow Width Chassis

Provides improved travel along narrow aiseways and access through doorways.

JLGEUROPE

JLG Industries (Europe), A Division of JLG Industries, Inc.
Kilmartin Place, Tannochside Park,
Uddingston, G71 5PH, Scotland.
Tel: 01698 811005
Fax: 01698 811055

www.jlg.com

