

JLG 400 SERIES



- Choice of models with working heights from 14 m to 16 m*
- Fast boom and drive speeds improve productivity.
 - Multiple simultaneous boom functions to get to the job quicker
 - Proportional controls achieve smoother movement for operator comfort
 - Excellent manoeuvrability for positioning of machine and platform
 - Use in all driving conditions
- Increased platform capacity if required**

* Model 400S - 14.02 m working height
Model 460SJ - 15.85m working height

** Model 400S only

For more details check the JLG Technical Specification Guide or ask your local JLG representative.



Oscillating axle option for tough travel

Provides increased traction when travelling.



Controls designed for ease of operation

Easier to operate when positioning and controlling movement.



Optional Increased capacity*

Allows for extra materials in the platform.

*Model 400S only.



Greater serviceability

Improved access with an engine swing-out tray.



Articulating Jib

Allows for greater versatility when positioning the platform around obstacles.

*Model 460SJ only.



Semi-track Option with Floating idler

Assists when travelling through mud, sand and snow.

JLGEUROPE

JLG Industries (Europe), A Division of JLG Industries, Inc.
Kilmartin Place, Tannochside Park,
Uddingston, G71 5PH, Scotland.
Tel: 01698 811005
Fax: 01698 811055

www.jlg.com

