

ARTICULATING BOOM LIFTS

1250AJP

Platform Height	38.10 m
Horizontal Outreach	19.25 m
Up and Over Height	18.44 m
Swing (Continuous)	360°
Platform Capacity – Restricted	450 kg
Platform Capacity – Unrestricted	230 kg
Platform Rotator (Hydraulic)	180°
Jib – Overall Length	2.44 m
Jib - Range of articulation	130° Vertical (+75°/-55°)
JibPLUS® - Range of Articulation	125° Horizontal
A. Platform Size	0.91 m x 2.44 m
B. Overall Width (Axles Retracted)	2.49 m
Overall Width (Axles Extended)	3.81 m
C. Tailswing (working condition)	2.26 m
D. Stowed Height	3.05 m
E. Stowed Length	11.46 m
F. Wheelbase	3.81 m
G. Ground Clearance	0.30 m
Gross Vehicle Weight*	19,958 kg
Maximum Ground Bearing Pressure	7.03 kg/cm ²
Drive Speed	5.2 km/h
Gradeability	45%
Tyres	445/50D710 Foam Filled
Axle Oscillation	0.30 m
Turning Radius – Inside (Axles Retracted)	4.39 m
Turning Radius – Inside (Axles Extended)	2.44 m
Turning Radius – Outside (Axles Retracted)	6.86 m
Turning Radius – Outside (Axles Extended)	5.89 m
Diesel Engine - Deutz BF 4M 2011	65 kW
Fuel Tank Capacity	117 L
Hydraulic Reservoir	202 L
Auxiliary Power	12V DC

*Certain options or country standards will increase weight.
Specifications may change to meet country standards or with the addition of optional equipment.



JLG MODEL 1250AJP

