

## JLG 600 SERIES



- Choice of models with working heights from 20 m to 22 m \*
- Fast boom and drive speeds improve work productivity
- Multiple simultaneous boom functions get you to the job quicker
- Proportional controls achieve smoother movement for operator comfort
  - Excellent manoeuvrability for positioning of machine and platform
- Handle the roughest of terrain with increased engine power

\* Model 600S & 600SJ - 20 m working height  
Model 660SJ - 22 m working height

For more details check the JLG Technical Specification Guide or ask your local JLG representative.



### Oscillating axle option for tough travel

Provides increased traction when travelling.



### Controls designed for ease of operation

Easier to operate when positioning and controlling movement.



### Articulating Jib\*

Allows for greater versatility when positioning the platform around obstacles.  
\* Models 600SJ and 660SJ.



### Diagnostic Ground Control Console

Console features three-dimensional decal plus diagnostic maintenance sensors.



### Low mount platform access

Step-in entry height and high strength railings provide operator both convenience and security.



### Greater serviceability

Improved access with an engine swing-out tray.

### JLGEUROPE

JLG Industries (Europe), A Division of JLG Industries, Inc.  
Kilmartin Place, Tannochside Park,  
Uddingston, G71 5PH, Scotland.  
Tel: 01698 811005  
Fax: 01698 811055

[www.jlg.com](http://www.jlg.com)

