PERSONNEL LIFTS JLG MODEL 15MVL

Features

- Heavy Duty Planetary Gear Drive Motors
- Low Maintenance Anodized Aluminum Mast
- Quick-Change Platform Mounting
- Extension 0.66m x 1.25m Platform
- Safety Interlocked Controls
- Heavy Duty Pistol-Grip Joystick
- · Direct Electric Drive
- Point & Go®One-Hand Drive and Steer System
- Proportional Drive and Elevate Controls
- Automatic Pothole Protection System
- 1-1/2 Degree Tilt Alarm and Control
- Automatic Battery Charger
- Two Sealed 100 A/hr Maintenance Free Batteries
- Key Lock Main Power Switch
- Automatic Power-Off Battery Saver Control
- Battery Discharge Indicators— Platform and Base
- · Non-Marking Tyres
- Transportation Tie Downs
- Built-In Fork Truck Pockets
- Lanyard Attachment Anchor
- Hourmeter
- All Motion Alarm
- AC Power Cable to Platform
- 32 cm Rear Wheels, 20 cm Front Castors
- Flashing Amber Beacon
- Horn
- ANSI, OSHA, CSA & CE Compliant

Specifications

Dimensions

Platform Height	4.67m
Working Height	6.50m
Drive Height	4.67m
Stowed Height	1.98m
Platform Entry Height	0.48m

Platform Capacity

Oversized Platform	227 kg
Narrow Platform	227 kg
Extension Platform	227 kg

Platform Size (W x L)

0.56m x 0.64m
0.66m x 0.66m
0.66m x 1.25m

Overall Vehicle Length

Chassis Length	1.36m
Chassis Echigin	1.00111

Extension Platform

Retracted	1.36m
All Other Platforms	1.36m

Overall Vehicle Width:

Chassis Width	0.75m
Extension Platform	0.80m
All Other Platforms	0.75m

Weight

Narrow Platform	1,055 kg
Extension Platform	1,086 kg

Drive Maximum Speed

5.6 km/h
1.0 km/h
Zero
30%
5 cm

Wheel Diameter & Width

Rear Drive & Steer Wheels	32 cm x 10 cm
Front Castor Wheels	20 cm x 6 cm
Tyre Material	Non-Marking

Batteries

Two Sealed 100 A/hr Glass Mat (AGM)

Battery Charger 25 Amp Automatic 5-Hour Charge

Drive System

4 Brush Direct Electric Motors (planetary gear)

Pothole Protection System

Automatic — Mechanical

Accessories & Options

Platform Options

Narrow Slide-Bar Front Entry

0.56m x 0.64m

Extension Slide-Bar Front Entry

0.66m x 0.66m – Retracted 0.66m x 1.25m – Extended

Security

Programmable 4-Digit Security Lock

Crane Hook

Lifting Eye for a Crane Hook

Fluorescent Light Tube Caddy

Tool Tray

0.20m x 0.46m x 0.13m





Printed in UK FORM No.: MVL-0306-3000 PART NO.: MVL001-ENGLISH JLG Industries Inc.
Polaris Avenue 63
2132 JH Hoofddorp
The Netherlands
Tel: +31 (0)23 565 5665
Fax: +31 (0)23 557 2493
e-mail address: europe@jlg.com