

Features

- Heavy Duty Planetary Gear Drive Motors
- Heavy Duty Pistol-Grip Joystick
- Direct Electric Drive
- Point & Go® One-Hand Drive and Steer System
- Low Maintenance Anodised Aluminium Mast
- Proportional Drive and Elevate Controls
- Two Sealed 100 A/hr Maintenance-Free Batteries
- Automatic Five-Hour Battery Charger
- Battery Discharge Indicators— Platform and Base
- Strobe Lights Front & Rear
- Programmable Motion Alarm
- Slope Cut-out Control Interlock
- Stand-on Foot Switch Operation enable Control
- Platform Gate Operation Interlock
- Adjustable Height Material Tray
- Non-Marking Tyres
- Built-In Fork Truck Pockets
- Lanyard Attachment Anchor
- Hourmeter
- Horn
- Transportation Tie Downs
- Automatic Power-Off Battery Saver Control
- Side and Front Bumpers
- ANSI, OSHA, CSA & CE Compliant

Specifications

Dimensions:

Platform Height	3.05m
Working Height	4.88m
Max Drive Height	3.05m
Stowed Height	1.42m
Platform Entry Height	0.33m

Platform Capacity:

Stock Picking Platform	159 kg
Carry Deck Capacity	113 kg
Material Tray Capacity	113 kg

Platform Size (W x L):

Operator Platform	0.69m x 0.51m
Material Tray	0.66m x 0.66m
Carry Deck	0.56m x 0.58m

Overall Vehicle Length:

Chassis Length	1.52m
----------------	-------

Overall Vehicle Width:

Chassis Width	0.84m
Chassis Width w/o bumper	0.75m

Weight:

	500 kg
--	--------

Drive Maximum Speed:

Platform Lowered	5.6 km/h
Platform Elevated	1.0 km/h
Turning Radius	Zero
Gradeability	30%
Ground Clearance	5 cm

Wheel Diameter & Width:

Rear Drive & Steer Wheels	32 cm x 10 cm
Front Castor Wheels	20 cm x 6 cm
Tyre Material	Non-Marking

Batteries:

Two Sealed 100 A/hr Glass Mat (AGM)	
Battery Charger	25 Amp, Automatic 5-hour charge

Drive System:

4 Brush Direct Electric Motors (planetary gear)

Accessories & Options

- Programmable 4-Digit Security Lock
- Guide Roller System

