

## JLG 800 SERIES



- Choice of models with up to 26 m working height
- Exclusive QuikStik™ Boom provides faster duty cycles up and down
  - Fast boom and drive speeds improve work productivity
  - Multiple simultaneous boom functions get you to the job quicker
- Proportional controls achieve smoother movement for operator comfort
- Excellent manoeuvrability for positioning of machine and platform
- Handle the roughest of terrain with increased engine power

For more details check the JLG Technical Specification Guide or ask your local JLG representative.



### The Industry's Best Reach Envelope

Delivers 9.75 m of up and over clearance, and over 15.5 m horizontal outreach\*.  
\*Model 800A - 16.15 m  
Model 800AJ - 15.74 m



### Articulating Jib\*

Allows for greater versatility when positioning the platform around obstacles.  
\*Model 800AJ only.



### QuikStik™ Boom provides optimum productivity

Unique feature that links two lifting actions, allowing the operator to go from the ground level to full elevation in less than 50 seconds (the same applies when lowering the boom).



### Controls designed for ease of operation

Easier to operate when positioning and controlling movement.



### Oscillating axle option for tough travel

Provides increased traction when travelling.



### Greater serviceability

Improved access with an engine swing-out tray.

### JLGEUROPE

JLG Industries (Europe), A Division of JLG Industries, Inc.  
Kilmartin Place, Tannochside Park,  
Uddingston, G71 5PH, Scotland.  
Tel: 01698 811005  
Fax: 01698 811055

[www.jlg.com](http://www.jlg.com)

