


10

MRT4 Dual Circuit [320kg] The World's Number One

The MRT4, with dual circuit vacuum system technology, is built for versatility. It delivers 360° continuous rotation with 90° tilt from any rotation position. Using the extension arms and moveable pads, three extra frame configurations are possible to cover most load sizes on site or in the workshop. A variable length lifting arm may be specified, allowing easier fitting under soffits and overhangs.




Vacuum system	dual circuit:	1 pump, 2 vacuum tanks
Suitable for lifting	material properties:	gastight
	surface:	smooth
	example:	glass, plastic boards, ceramic plates, sheet metals, coated boards
Suction cup type	approx diameter:	305mm
Suction cup quality	description:	black rubber, not abrasion resistant, heat resistant up to 100°C
Number of suction cups	cups:	4
Loading capacity	vertical:	320kg
of frame	horizontal:	320kg
Weight of lifter	approx:	58kg
Structural depth	approx:	292mm
Output	approx:	1.5m ³ /h
Voltage	pump:	12v DC from rechargeable battery
	battery charger:	110v/240v 50/60Hz single phase factory selectable
Standard accessories	standard:	4 x extension arms
Optional accessories	optional:	variable length lifting arm, extra length extension arms

MRT4





three extra frame configurations to cover most load sizes



- Manual 360° lockable rotation (continuous)
- Manual tilting from vertical to horizontal



- 12v rechargeable battery with integral 110v or 240v charger and battery energy gauge
- Audio-visual low vacuum alert
- Four extension arms allow alternative configurations



MRT4 · Variable Length Lifting Arm - 600mm



W WWW



Dual Circuit MRT4 variable length lifting arm \cdot Code VGL18

